



## Product Data

rev 2012/04

### Product Description

Duet colors are water based dyes. Concrete floors can be dyed as they are densified by mixing the Duet color kit with Lythic Densifier. An alternate application, Duet colors can also be mixed with water and applied before sealing or densifying.

### Primary Applications

Commercial, Institutional, and Residential concrete surfaced floors.

Also suitable for application to cementitious bonded toppings.

Duet colors are for interior not exterior concrete.

### Advantages

- Water based product, requires no solvents for application
- No noxious fumes
- Saves labor when used in Lythic Densifier
- Even color distribution in one application
- No penetrating agents required
- Can be applied with water and sealed with top coat



### Packaging

Duet colors are sold in concentrated 10 oz. kits to add to 1 gallon of Lythic Densifier or alternately, 1 gallon of clean water.

Larger kits can be shipped on request.





## **Preparation**

Remove surface laitance, topical compounds and any residue that can impede penetration before applying Duet colors. This process may be simply mechanical scrubbing, sanding screens or chemical strippers. In the polished concrete process grind, hone and polish to 400 before applying.

## **Application**

Add Duet color kit into one gallon of Lythic Densifier or a gallon of water. Duet will blend and mix without vigorous stirring or shaking.

Application of color in a test area is recommended to confirm desired results before beginning the project.

Apply with a pump sprayer at a rate of 400 sq. ft. per gallon. Follow the spray down by back rolling with a dampened microfiber roller to even out the color. Walking into the wet areas will not damage or affect the quality of the color in the floor.

When dry, remove excess dye with a light scrubbing using an auto scrubber, or with the final diamond tool step of the polishing process.

Duet in water applications requires a top coat sealer to protect the dyed surface. If no densifier is applied, a wax maintenance program is recommended.

Maintain finished floors with a pH neutral cleaner on a regular cleaning schedule to extend the life of the finished floor.

---

## **Cleanup**

Clean equipment with warm soapy water. Dispose of residue or excess material in accordance with local, state and federal guidelines.

## **Storage**

Store closed containers at 40-80 degrees F.

Do not allow to freeze.

Shelf life is 6 months from date of manufacture.

## **Warranty**

Lythic Solutions guarantees that that the product will be of consistent color and mixture when received. The manufacturer has no control over the use of this product; therefore, no warranty, expressed or implied, is or can be made to either the effects or results of such use. Lythic Solutions obligation under this warranty shall be limited to re-funding the purchase price or replacing material proven defective

rev 2012/04

