

Consolideck® DailyKlean Cleaning Specification

Specifier Note: The information provided below is intended to guide the Architect in developing specifications for products manufactured by PROSOCO, Inc. and should not be viewed as a complete source of information about the product(s). The Architect should always refer to the Product Data Sheet and MSDS for additional recommendations and for safety information

Specifier Note: Paragraph below is for PART 1 GENERAL, Quality Assurance.

Test Area

Test a minimum 4 ft. by 4 ft. area on each type of masonry. Use manufacturer's application instructions. Let the test panel dry 3 to 7 days before inspection. Keep test panels available for comparison throughout the cleaning project.

Specifier Note: Paragraphs below are for PART 2 PRODUCTS, Manufacturers and Products.

Manufacturer: PROSOCO, Inc., 3741 Greenway Circle, Lawrence, KS 66046. Phone: (800) 255-4255; Fax: (785) 830-9797. E-mail: CustomerCare@prosoco.com

Product Description

Consolideck® DailyKlean is a specially designed concentrated maintenance cleaner for concrete floors, including floors treated with lithium-silicate hardening/densifying products. Though specifically designed for lithium-silicate hardened and densified floors, DailyKlean is an effective maintenance cleaner for almost any concrete floor. The specialized blend of degreasers and detergents removes most common soiling found on concrete floors.

Technical Data

FORM: clear orange liquid, fresh clean odor

SPECIFIC GRAVITY: 0.999

pH: 8.6

WEIGHT/GALLON: 8.32 pounds

ACTIVE CONTENT: not applicable

TOTAL SOLIDS: not applicable

VOC CONTENT: less than 1% maximum

FLASH POINT: greater than 200 degrees F (greater than 93 degrees C) ASTM D 3278

FREEZE POINT: 31 degrees F (-0.5 degrees C)

SHELF LIFE: 2 years in unopened, factory-sealed container

VOC: Compliant with all national, state and district VOC regulations.

Specifier Note: Paragraphs below are for PART 3 EXECUTION, Installation.

Application

Before applying, read "Preparation" and "Safety Information" sections in the Manufacturer's Product Data Sheet for Consolideck® DailyKlean. Refer to the Product Data Sheet for additional information about application.

Dilution

For normal cleaning, dilute 1 ounce of cleaner per 1-gallon of fresh water. For deep cleaning, dilute 2-ounces of cleaner per 1-gallon of fresh water. For PAX packaging, dilute one 4-ounce PAX per 5-gallon of fresh water.

Application Instructions

Apply with a mop or automatic scrubber. Rinsing is not necessary for routine surface cleaning. Mop up spent cleaner and dissolved contaminants, or allow automatic scrubber

to vacuum it up. After deep cleaning, rinse well with fresh water. Do not let cleaner dry on the floor. Buff the cleaned floor with a white pad to increase the shine.

Cleanup

Clean tools and equipment using fresh water.