

Consolideck® Wax & Cure Remover Cleaning Specification

Specifier Note: The information provided below is intended to guide the Architect in developing specifications for products manufactured by PROSOCO, Inc. and should not be viewed as a complete source of information about the product(s). The Architect should always refer to the Product Data Sheet and MSDS for additional recommendations and for safety information.

Specifier Note: Paragraph below is for PART 1 GENERAL, Quality Assurance.

Test Area

Test a minimum 4 ft. by 4 ft. area on each type of masonry. Use manufacturer's application instructions. Let the test panel dry 3 to 7 days before inspection. Keep test panels available for comparison throughout the cleaning project.

Specifier Note: Paragraphs below are for PART 2 PRODUCTS, Manufacturers and Products.

Manufacturer: PROSOCO, Inc., 3741 Greenway Circle, Lawrence, KS 66046. Phone: (800) 255-4255; Fax: (785) 830-9797. E-mail: CustomerCare@prosoco.com

Product Description

Consolideck® Wax & Cure Remover is a water-rinsable cleaner designed to prepare concrete floors for hardening and densifying by removing old coatings that can block treatments from penetrating or clog up heads on grinding and polishing equipment. The low-odor cleaner quickly removes a variety of floor waxes and acrylics, including low-solids cure and seals.

Technical Data

FORM: amber liquid, light citrus odor

SPECIFIC GRAVITY: 1.05

pH: not applicable

WT./GAL: 8.76 pounds

ACTIVE CONTENT: not applicable

TOTAL SOLIDS: not applicable

FLASH POINT: > 200 degrees F (> 93 degrees C) ASTM D 3278

FREEZE POINT: not applicable

SHELF LIFE: 2 years in unopened, factory-sealed container

VOC Content: 4% maximum. Consolideck® Wax & Cure Remover is compliant with all national, state and district VOC regulations.

Limitations:

- Surfaces are slippery during application. Use appropriate caution.
- Product efficiency is reduced in cold temperatures.
- May damage synthetic or reflective glass. Always protect.

Specifier Note: Paragraphs below are for PART 3 EXECUTION, Installation.

Application

Before applying, read "Preparation" and "Safety Information" sections in the Manufacturer's Product Data Sheet for Wax & Cure Remover.

Dilution

The product should be diluted with clean water, based upon its intended use:

For removal of light wax build-up, dilute 1 part product to 10 parts water.

For removal of heavy wax build-up, dilute 1 part product to 3 parts water.

For removal of low-solids cure and seals, use product at full strength.

Coverage

Coverage rates vary based on concrete porosity and texture. Anticipated coverage rate is 300-500 square feet per gallon of prepared cleaner.

Application Instructions

1. Apply product with low-pressure spray.
2. Allow to dwell for 5-10 minutes.
3. Scrub with a stiff bristle brush or a mechanical scrub machine.
4. Take up as much spent cleaner and dissolved coating as possible.
5. Rinse or mop the floor with fresh water if needed.

Cleanup

Clean tools and equipment with fresh water.