




## Husqvarna FS 413

*Our highly versatile FS 413 is a compact petrol push floor saw developed with a clear focus on your comfort. Ideal for small to mid-sized service and repair jobs in asphalt and concrete. Cuts up to 189 mm deep.*



### LOW VIBRATIONS

Engine and blade shaft mounting system increases comfort and gives excellent cutting performance.



### LOW MAINTENANCE

The IntelliSeal blade shaft system allows for a minimum of 250 maintenance-free hours without daily greasing of bearings.



### EASY TO ADJUST THE BLADE

Spring-assisted screw feed facilitates blade adjustment in and out of the cut.



### EASY TO TRANSPORT

Compact saw that is easy to lift.

## Features Husqvarna FS 413

- Provides a closer and more comfortable position to the cutting side for easier alignment and straighter cuts. Handle can also be folded for transport.
- Adjustable for all blade diameters.

TECHNICAL SPECIFICATION	
Motor manufacturer	Honda
Motor spec	GX390
Max output (As rated by the engine manufacturer)	8.7kW / 11.7 hp
Engine/motor RPM	pos1:3600 rpm
Cylinders	1
Number of strokes	4-stroke engine
Cylinder displacement	389 cm <sup>3</sup> / 23.7 cu.inch
Cylinder bore	88 mm / 3.5 inch
Cylinder stroke	64 mm / 2.5 inch
Fuel tank volume	6.1 lit / 1.61 gal.
Air filter type	Cyclone dry dual
Starter	Recoil
Engine cooling	Air
Belt	PolyV
Oil capacity, l	1.1 lit
Diamond blade, max	500 mm / 20"
Max cutting depth	189 mm / 7.6 inch
Spindle diameter	25.4 mm / 1"
Blade depth control	Patent-pending spring assist raise/lower with positive lock-type hand crank
Blade flange	114 mm / 4.5"
Blade shaft RPM	2600 rpm
Arbor size	25.4 mm / 1"
Axle front	22 mm / 0.87 inch
Handle bars	Adjustable in height
Primary wheel size	Outside diameter: 114.3 Wheel width: 38.1 Inner bore: 16 mm / Outside diameter: 4.5 Wheel width: 1.5 Inner bore: 0.63"
Secondary wheel size	Outside diameter: 203.2 Wheel width: 50.8 Inner bore: 16 mm / Outside diameter: 8 Wheel width: 2 Inner bore: 0.63"
Blade guard attachment	Slip-on
Blade guard type	Slip-on
Weight	163 kg / 359.35 lbs
Weight incl. packaging	178 kg / 392.42 lbs
Product size, LxWxH	1550x655x1200 mm / 61.02x25.79x47.24 inch
Sound power level, guaranteed (LWA)	104 dB(A)
Sound pressure	87 dB(A)
Hand arm vibration (Aeq)	3.4 m/s <sup>2</sup>

