




Husqvarna Soff-Cut 150 D

The Husqvarna Soff-Cut 150 D saw was designed especially for the contractor who wants a no-hassle way to make decorative cuts. It was also designed to be economical and durable. The 150 D has a low noise, low vibration 4-1/2 horsepower Robin engine and is ideal for large and small jobs alike. This saw, along with the Husqvarna Soff-Cut 50 handheld saw, is the perfect solution to your decorative jobsite needs.



SOFF-CUT™ TECHNOLOGY

Husqvarna Soff-Cut is a unique patented system for early entry concrete sawing. This technology enables concrete to be cut within the first one or two hours of finishing and before final set. Husqvarna Soff-Cut™ provides the best solution for minimizing the risk of random cracking, and it simplifies the working process, compared to conventional sawing.

Features Husqvarna Soff-Cut 150 D

- Recommended for light to medium duty use on decorative cuts, driveways and parking lots.
- Low noise and low dust blade block enclosure.
- 4-1/2 engine with cyclone air filter.
- Mechanical blade depth control.
- Non-marking and non-stick polyurethane wheels.
- High strength single piece frame.
- Folding handle.
- Center lifting handle.
- Distinctive roll cage style framework.
- Patented safety arbor.
- Easy pull start engine.
- Turns ragged, chipped or raveled saw joints into beautifully beveled or radius edges.
- A preset depth of cut - no fumbling with depth screws and bolts to adjust for proper radius or V-blade cutting.
- Self-aligning guide wheels - guarantee proper blade alignment with saw joint every time.
- Four (4) different size guide wheels, for 1/8", 1/4", 3/8" and 1/2" saw joint, assures optimum performance.
- Bronze bushing mounted guide wheels allows for smooth operation for consistent width cut.
- Larger diameter blade block shafts, front and rear for increased rigidity and strength.
- Integrated weight block - maintains proper weight balance for consistent cut.
- Stainless steel front diverter - reduces dust blown out.

TECHNICAL SPECIFICATION	
Motor manufacturer	Subaru
Motor spec	EX13
Max output (As rated by the engine manufacturer)	3.2 kW / 4.3 hp
Engine/motor RPM	pos1:4000 rpm
Cylinders	1
Number of strokes	4-stroke engine
Cylinder displacement	7.69 cu. inch
Cylinder bore	2.28 inch
Cylinder stroke	1.89 inch
Fuel tank volume	0.7 gal.
Starter	Recoil
Engine cooling	Air
Number of belts	1
Displacement, l	0.126 lit
Oil capacity, l	0.6 lit
Output RPM	3800 rpm
Diamond blade, max	6"
Max cutting depth	1.19 inch
Blade depth control	Manual
Blade control	Manual
Blade shaft diameter	0.75 inch
Blade flange	3"
Blade shaft RPM	3800 rpm
Axle front	0.75 inch
Rear axle diameter	0.75 inch
Handle bars	Fixed
Primary wheel size	Outside diameter: 3 Wheel width: 3 Inner bore: 0"
Secondary wheel size	Outside diameter: 3 Wheel width: 3 Inner bore: 0"
Weight	102 lbs
Weight incl. packaging	108 lbs
Product size, LxWxH	68x19x33.5 inch
Sound power level, guaranteed (LWA)	99 dB(A)
Sound pressure	84 dB(A)
Hand arm vibration (Aeq)	7.9 m/s ²