



Husqvarna Soff-Cut 4200

The Husqvarna 4200 self-propelled dry-cutting gasoline saw has a low-noise enclosed design and is ideal for heavy-duty commercial, industrial and paving applications. The 4200 is designed for peak performance. Features include a 23 hp twin-cylinder gasoline engine, three-stage cyclonic air cleaner, oil cooler, full-pressure oil lubrication, hydraulic valve lifters, mechanical fuel pump and oil alert light. Multiple blade widths can be used, allowing different joint widths and crack control simultaneously.



SOFF-CUT™ TECHNOLOGY

Husqvarna Soff-Cut is a unique patented system for early entry concrete sawing. This technology enables concrete to be cut within the first one or two hours of finishing and before final set. Husqvarna Soff-Cut™ provides the best solution for minimizing the risk of random cracking, and it simplifies the working process, compared to conventional sawing.

Features Husqvarna Soff-Cut 4200

- Self-propelled gasoline saw with positraction drive, hydrostatic transmission and travel speed indicator.
- Switch-activated electronic adjustable handles.
- Electronic remote key start and choke.
- High-strength, lightweight aluminium frame.
- Switch-activated blade depth control and retractable guide.
- Patented dry-cut diamond blade, anti-ravel skid plate and arbor.
- Patented low-noise and low-dust blade block enclosure.
- Mechanical depth gauge.

TECHNICAL SPECIFICATION	
Motor manufacturer	Kohler
Motor spec	Kohler gasoline
Max output (As rated by the engine manufacturer)	17.2 kW / 23 hp
Cylinders	2
Number of strokes	4-stroke engine
Cylinder displacement	41.1 cu.inch
Cylinder bore	3.2 inch
Cylinder stroke	2.6 inch
Fuel tank volume	3.16 gal.
Starter	Electric
Engine cooling	Air
Number of belts	3
Displacement, l	674 lit
Oil capacity, l	1.9 lit
Output RPM	3500 rpm
Diamond blade, max	14"
Max cutting depth	3 inch
Blade depth control	Electric
Blade control	Electric Remote
Blade shaft diameter	1.5 inch
Blade flange	5.875 "
Blade shaft RPM	3500 rpm
Axle front	1 inch
Rear axle diameter	1 inch
Handle bars	Multi position
Primary wheel size	Outside diameter: 4 Wheel width: 4 Inner bore: 0"
Secondary wheel size	Outside diameter: 11 Wheel width: 4 Inner bore: 0"
Weight	488 lbs
Weight incl. packaging	568 lbs
Product size, LxWxH	89x30x40.25 inch

