



This hydraulically driven, forward self-propelled scraper removes the worst of today's soft goods, such as glued-down floors, gummy commercial carpet, VCT, sheet vinyl, rubber tile, linoleum, indoor and outdoor sport surfaces, roofing material, and more. The ergonomic features of this machine reduce operator fatigue while optimizing time and labor savings. The compact design makes it ideal for use in tight spaces.

5280 Specifications

| | | |
|-----------------------|------------------------------|----------------------------------|
| Power Supply | Electric | |
| Width | 17" | 43 cm |
| Height | 39" | 99 cm |
| Length | 27" | 69 cm |
| Weight | 263 lbs | 119 kg |
| Removable Weight | 37 lb front, 49 lb saddle | 16.8 kg front, 22.2 kg saddle |
| Weight (machine only) | 177 lb | 80.3 kg |
| Speed | 12-50 ft/min | 3.7-15.2 m/min |
| RPM | 1725 | 1425 |
| Voltage | 115 | 230 |
| Frequency | 60 Hz | 50 Hz |
| HP | 1 | .746 kW |
| Amps (full load) | 12 | 6.7 |
| Noise Emissions | 77 dB | |

Meets the requirements of the Machine Directive 2006/42/EC and EMC Directive 2004/18/EC. It is CE marked.

SAFETY

A. Tie-down/lifting bail

PERFORMANCE

B. Forward self-propelled control

COMFORT

C. Variable speed, 12 to 50 feet per minute

D. Self-contained, limited-maintenance hydraulic fluid

E. Removable 49-pound saddle weight helps increase or decrease down pressure and traction

F. Orbital action rotates the cutting blade to cut through a range of materials over various substrates; extends life cycle of machine while reducing maintenance costs

INCLUDED WITH THE 5280

- 148 5" x 6" blade
- 5280-137W: 6mm T-handle wrench
- One-year manufacturer's warranty on parts and labor

RECOMMENDED ACCESSORIES

6280-505

- Swivel head rotates to allow continuous contact with the floor

6280-500

- Swivel head allows for continuous contact with the floor and is specifically for razor blades