

# 6280HD Gladiator®

## HYDRAULIC WALK-BEHIND SCRAPER



6280HD-HER, 6280HD-SUN



The Gladiator removes the worst of today's hard and soft goods, such as ceramic tile, wood floors, thin-set, sheet vinyl, linoleum, and more. Its compact design makes it ideal for use in confined spaces, while the side slide weights add extra head pressure when forward and improved traction when moved over the back wheels.

### 6280HD Specifications

Power Supply	Electric	
Width	17.75"	45 cm
Max. Height	46.75"	119 cm
Height (handle folded)	30"	76 cm
Max. Length	49.5"	126 cm
Length (handle folded)	29.5"	75 cm
Weight	490 lb	222.3 kg
Removable Weight	78 lb front, 43 lb side	35.4 kg front, 19.5 kg side
Weight (machine only)	369 lb	167.4 kg
Speed	up to 30 ft/min	9.1 m / min
RPM	1725	1425
Voltage	115	230
Frequency	60 Hz	50 Hz
HP	1.5	1.12 kW
Amps (full load)	14.7	10.5
Noise Emission	77 dB	

Meets the requirements of the Machine Directive 2006/42/EC and EMC Directive 2004/108/EC. It is CE marked

### SAFETY

- A.** Rounded front-weight design better deflects loose material away from machine during use
- B.** Tie down/lifting bails

### COMFORT

- C.** Ergonomically designed, adjustable-position hand grips; hydraulic self-propelled forward and reverse; variable speed, 10 to 30 feet per minute; optional manual drive with removal of drive pins; system for throttle/speed control and smooth transitions
- D.** Six handle positions for work under racks and in other confined areas; collapses to save space during transport and storage

### PERFORMANCE

- E.** Self-contained, limited-maintenance hydraulic fluid
- F.** Secure-mount side slide weights adjust scraper-head pressure; side slide weights add extra head pressure when forward and improved traction when moved over the back wheels
- G.** Adjustable, self-cleaning, industrial-grade, siped wheels for improved traction over smooth or slippery surfaces; clip-pin removal allows for easy nonpowered maneuvering
- H.** Motor equipped with thermal-overload-protection circuit breaker that protects against strain or electrical overload
- I.** Orbital action rotates the cutting blade to cut through a range of materials over various substrates; extends life cycle of machine while reducing maintenance costs
- J.** Design incorporates nine isolators for the toughest jobs

### INCLUDED WITH THE 6280HD

- 6280HD-250 Transport Wheel Assembly 6280HD
- Kit 5174 includes :
  - 6265-BD: 90 degree, 3" x 8" self-scoring, bevel down
  - 6276-BU: 45 degree, 3" x 10" self-scoring, bevel up
  - 7050-200: 3" x 6" premium blade
  - 7280-2C: 30-degree angle attachment
  - 7280-4: retainer cap assembly
  - 7280-6: 6" cutting head
  - 7281-1: 1" x 6" angle shank w/ carbide shank
- One-year manufacturer's warranty on parts and labor