



Husqvarna DE 110

This versatile HEPA dust extractor is compact and easy to transport, yet powerful. It is equipped with a user friendly HMI that monitors performance and an e-flow function that automatically adjusts the air flow, enabling stable air flow and extending intervals between filter-cleanings. Its high water protection allows fast and efficient decontamination. It also features embedded connectivity allowing you to swiftly monitor location, run-time, service and filter status along with other valuable usage data.



Easy to transport

Thanks to its compact size and light weight, the dust extractor is easy to transport. Smart details, such as lifting hooks, the possibility to attach hoses, wand and floor tool to the machine and the ability to drive it on its two wheels allow for smooth manoeuvring.



High safety standards

The dust extractor complies with the latest H-class standards for dust extractors for heavy-duty usage. It contains a HEPA filter (with EN1822 certification) which is separated from the pre-filter. An integrated filter alarm with adjustable hose-diameter indicates when it is time to clean the filter. Cleaning can be done by simply pressing a button.

Continuous high performance

The ingenious e-flow system automatically adjusts air flow to prolong time between filter cleanings, allowing operators to work longer without interruption.



Easy to clean and maintain

The high water protection standard allows for easy cleaning and decontamination of the machine. The HMI gives warnings on operational maintenance for early and on-site trouble-shooting.



FEATURES

- Continuous high performance
- High safety standards
- Easy to transport
- Easy to clean and maintain
- Improved Longopac® attachment system
- Optimised accessory range
- Operate more sustainably with e-flow

Technical Specifications

MOTOR

Phases	1
Voltage	120 V
Rated current	9.5 A
Frequency	50–60 Hz
Max. vacuum	200 mbar
Rated input power	1.1 kW

Product size height	1000 mm
Product size length	670 mm
Product size width	400 mm
Weight	25 kg

SPECIFICATIONS

Air Flow	225 m ³ /h
Max. vacuum	200 mbar

PACKAGING

Packaging length	1190 mm
Packaging width	745 mm
Packaging height	470 mm
Packaging volume	416.68 dm ³