



Description

HiperGuard™ is a penetrating guard that can be applied to a concrete surface at the end of the polishing process. It makes the concrete significantly more resistant to fats, oils and water, but still allows the concrete to breathe. It works by lining the capillaries on a concrete surface. This creates significantly more surface tension, which prevents various substances absorbing into the concrete.

Benefits

- It is not a surface/topical sealer and therefore cannot blister, wear off or discolor.
- Enables the concrete to breathe.
- Can enrich the color of the concrete.

HUSQVARNA CONSTRUCTION PRODUCTS

17400 West 119th Street, Olathe, KS 66061 USA
Tel 800-288-5040 Fax 800-825-0028
www.husqvarnacp.com

Mixing Instructions

All Husqvarna HiperGuard™ products are in a ready to use container. There is no need for dilution.

Application

1. Apply Husqvarna HiperGuard™ to a clean/dry surface using a pump sprayer, spraying product onto the floor.
2. Apply a single coat using enough to completely wet the surface for 30 seconds without creating puddles or rundown.
3. Using a Micro-fiber mop, mop the product uniformly around the floor.
4. Let HiperGuard™ completely dry (recommended 1 hours time will vary depending on extreme temperatures). Once HiperGuard™ is completely dry, a film will cover the floor.
5. Next place a hogshair pad underneath a Husqvarna grinder or propane burnisher and burnish the excess film off the floor. A second coat of HiperGuard™ may be necessary.



Packaging

Husqvarna HiperGuard™ is available in 1 gallon, 5 gallon pails and 55 gallon drums.

Cleaning

Application equipment (pump sprayers/micor-fiber mops) can be cleaned with water if still wet with product.

Shelf Life

Shelf life of HiperGuard™ in original tightly closed container is 3 years from date of manufacture. Do not allow the accumulation of water, dirt, or other contaminants. It is recommended that HiperGuard™ be stored at room temperature. Do not allow HiperGuard™ to freeze.

Approximate Coverage

1 gallon of HiperGuard™ will cover approximately 1,000 square feet depending on the porosity of the concrete.

Health and Safety

Refer to MSDS sheets.

HUSQVARNA CONSTRUCTION PRODUCTS

17400 West 119th Street, Olathe, KS 66061 USA

Tel 800-288-5040 Fax 800-825-0028

www.husqvarnacp.com